

SaniForce[®]

Air-Operated Double Diaphragm Pumps



unleash the
POWER

Portable, easy-to-clean, quick knockdown design

- Four models with maximum flow rates up to 150 gpm (567.8 lpm)
- All fluid contact materials are **FDA-Compliant** and meet CFR Title 21
- Featuring Graco's durable, lube-free, non-sticking air valve
- Bolt-through and overmolded diaphragm options available

Ordering Information

SANIFORCE 515, 1.0 IN (25.4 MM) SANITARY CLAMP CONNECTION

Part Number	Kits	Seats/ O-rings	Balls	Diaphragms
FD5111	FK5111	SST/PTFE	PTFE	PTFE
FD5113	FK5113	SST/PTFE	PTFE	Overmolded PTFE
FD5122	FK5122	SST/PTFE	Santoprene	Santoprene
FD5611	FK5611	SST/EPDM	PTFE	PTFE
FD5613	FK5613	SST/EPDM	PTFE	Overmolded PTFE
FD5622	FK5622	SST/EPDM	Santoprene	Santoprene

SANIFORCE 1040, 1.5 IN (38.1 MM) SANITARY CLAMP CONNECTION

Part Number	Kits	Seats/ O-rings	Balls	Diaphragms
FD1111	FK1111	SST/PTFE	PTFE	PTFE
FD1122	FK1122	SST/PTFE	Santoprene	Santoprene
FD1211	FK1211	SST/EPDM	PTFE	PTFE
FD1222	FK1222	SST/EPDM	Santoprene	Santoprene
FD1113	FK1113	SST/PTFE	PTFE	Overmolded PTFE
FD1213	FK1213	SST/EPDM	PTFE	Overmolded PTFE
FD1132	FK1132	SST/PTFE	Polychloroprene	Santoprene
FD1232	FK1232	SST/EPDM	Polychloroprene	Santoprene

SANIFORCE 1590, 2.0 IN (50.8 MM) SANITARY CLAMP CONNECTION

Part Number	Kits	Seats/ O-rings	Balls	Diaphragms
FD2111	FK2111	SST/PTFE	PTFE	PTFE
FD2122	FK2122	SST/PTFE	Santoprene	Santoprene
FD2211	FK2211	SST/EPDM	PTFE	PTFE
FD2222	FK2222	SST/EPDM	Santoprene	Santoprene
FD2113	FK2113	SST/PTFE	PTFE	Overmolded PTFE
FD2213	FK2213	SST/EPDM	PTFE	Overmolded PTFE
FD2132	FK2132	SST/PTFE	Polychloroprene	Santoprene
FD2232	FK2232	SST/EPDM	Polychloroprene	Santoprene

SANIFORCE 2150, 2.5 IN (63.5 MM) SANITARY CLAMP CONNECTION

Part Number	Kits	Seats/ O-rings	Balls	Diaphragms
FD3111	FK3111	SST/PTFE	PTFE	PTFE
FD3122	FK3122	SST/PTFE	Santoprene	Santoprene
FD3211	FK3211	SST/EPDM	PTFE	PTFE
FD3222	FK3222	SST/EPDM	Santoprene	Santoprene
FD3113	FK3113	SST/PTFE	PTFE	Overmolded PTFE
FD3213	FK3213	SST/EPDM	PTFE	Overmolded PTFE
FD3132	FK3132	SST/PTFE	Polychloroprene	Santoprene
FD3232	FK3232	SST/EPDM	Polychloroprene	Santoprene

Technical Specifications

	SaniForce 515	SaniForce 1040	SaniForce 1590	SaniForce 2150
Maximum fluid working pressure	100 psi (7 bar, 0.7 MPa)	120 psi (8 bar, 0.8 MPa)	120 psi (8 bar, 0.8 MPa)	120 psi (8 bar, 0.8 MPa)
Air pressure operating range	20-100 psi (1.4-7 bar, 0.14-0.7 MPa)	20-120 psi (1.4-8 bar, 0.14-0.8 MPa)	20-120 psi (1.4-8 bar, 0.14-0.8 MPa)	20-120 psi (1.4-8 bar, 0.14-0.8 MPa)
Maximum air consumption	28 scfm	50 scfm	130 scfm	175 scfm
Air consumption at 70 psi/20 gpm	N/A	18 scfm	42 scfm	70 scfm
Maximum free-flow delivery	16 gpm (61 lpm)	41 gpm (155 lpm)	100 gpm (379 lpm)	150 gpm (567.8 lpm)
Gallons (liters) per cycle	0.04 (0.15) with standard diaphragms 0.03 (0.11) with overmolded diaphragms	0.16 (0.61)*	0.5 (1.9)*	0.97 (3.67)*
Maximum suction lift	25 ft (7.6 m) wet, 15 ft (4.6 m) dry	29 ft (8.83 m) wet, 16 ft (4.87 m) dry	29 ft (8.84 m) wet, 14 ft (4.27) dry	29 ft (8.83 m) wet, 16 ft (4.87 m) dry
Maximum size pumpable solids	3/32 in (2.38 mm)	1/8 in (3.2 mm)	3/16 in (4.8 mm)	1/4 in (6.3 mm)
Air inlet size	1/4 npt(f)	0.5 in npt(f)	0.5 in npt(f)	0.5 in npt(f)
Fluid inlet/outlet size	1.0 in (25.4 mm) sanitary flange	1.5 in (38.1 mm) sanitary flange	2 in (50.8 mm) sanitary flange	2.5 in (63.5 mm) sanitary flange
Weight - All models	22.6 lb (10.25 kg)	55 lb (24.9 kg)	89 lb (40 kg)	147 lb (66.7 kg)
Instruction manual	3A1973	311879	311879	311879
Maximum fluid operating temperature is based on the following maximum diaphragm, ball, and seat temperature ratings				
Stainless steel	250°F (121.1°C)	250°F (121.1°C)	250°F (121.1°C)	250°F (121.1°C)
PTFE	220°F (104.4°C)	220°F (104.4°C)	220°F (104.4°C)	220°F (104.4°C)
Santoprene	180°F (82.2°C)	180°F (82.2°C)	180°F (82.2°C)	180°F (82.2°C)
EPDM	275°F (135°C)	275°F (135°C)	275°F (135°C)	275°F (135°C)

Provided by:



All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Call today for product information or to request a demonstration.

877.84GRACO (1-877-844-7226) or visit us at www.gracosaniforce.com

