

MICROCNX™ SERIES CONNECTORS

MicroCNX™ Connectors introduce a new category of aseptic micro-connectors that provide a simple, efficient method of connecting tubing for small-format biomanufacturing assemblies. MicroCNX connectors are the modern alternative to the cumbersome, industrial process of tube welding. Building on the inventiveness of CPC, the leader in single-use connection technology, the MicroCNX line of connectors is engineered specifically for the challenging conditions of biologic media transfer in bioprocessing, cell therapy and gene therapy applications.



SPECIFICATIONS

OPERATING PRESSURE

Up to 60 psi, 4.1 bar
Up to 75 psi, 5.1 bar for 48 hours

OPERATING TEMPERATURE

34°F to 104°F (1°C to 40°C)

TERMINATIONS

1/16", 3/32" 1/8" ID hose barb (1.6mm, 2.4mm, 3.2mm)

MATERIALS

Main Components: Polycarbonate (white), USP Class VI, ADCF

Seals: Silicone (clear), platinum-cured, USP Class VI, ADCF

Protective Cover: Polypropylene (teal), USP Class VI, ADCF

Membrane: Hydrophobic Polyethersulfone, USP Class VI

STERILIZATION

Gamma: Up to 50kGy irradiation.

Autoclave: One cycle up to 266°F (130°C) for 60 minutes

FEATURES

PINCH-CLICK-PULL →

Easy to use →

Genderless →

CPC Click →

BENEFITS

Intuitive three-step connection process reduces risk of operator error


Lowers risk of operator error and related performance, reliability and safety concerns

Eases single-use systems specifications with one part number for both halves

Audible confirmation of assembly with no additional hardware required

TYPICAL FLOW RATE

Cv Value Range: 0.04-0.27
for MicroCNX hose barb terminations



Cv values represent the approximate expected flow rate in gallons per minute of water at room temperature for a 1 PSI pressure drop. The flow is generally constrained by the smallest diameter, which in some cases will be the termination diameter and not the Nominal Flow Path.

Caution: CPC does not recommend the use of PVC tubing with the polycarbonate MicroCNX™ Series Connectors. Leachables from PVC tubing could be incompatible with polycarbonate material and affect product performance. Determining product application suitability is solely the customer's responsibility. CPC does not guaranty or warrant product suitability for any application or use.

NOTE

Validation and Extractables data can be requested at cpcworldwide.com/MicroCNX

DID YOU KNOW

MicroCNX connectors eliminate the need to purchase, calibrate, validate, maintain, and allocate clean room space for tube welding equipment.



SCAN

cpcworldwide.com/MicroCNX



COLDER PRODUCTS COMPANY

U.S.A.

PHONE: +1 (651) 645-0091
FAX: +1 (651) 645-5404
TOLL FREE: +1 (800) 519-7633

COLDER PRODUCTS COMPANY GMBH

Germany

PHONE: +49 6026 9973-0

COLDER PRODUCTS COMPANY LIMITED

Shanghai, China

PHONE: +86 21 2411 2666
TOLL FREE: +86 400 990 1978


MICROCNX™ SERIES DIMENSIONS AND WEIGHTS

POLYCARBONATE with teal cover For autoclave or gamma irradiation applications.



TERMINATION	METRIC EQ.	PART NO.	A	B	C	PART WEIGHT
1/8" HOSE BARB	3.2 mm	CNX17002HT	0.93 (23.6 mm)	2.25 (57.2 mm)	1.49 (37.8 mm)	0.27 oz (7.64 g)
3/32" HOSE BARB	2.4 mm	CNX17003HT	0.93 (23.6 mm)	2.16 (54.9 mm)	1.49 (37.8 mm)	0.27 oz (7.62 g)
1/16" HOSE BARB	1.6 mm	CNX17001HT	0.93 (23.6 mm)	2.05 (52.1 mm)	1.49 (37.8 mm)	0.27 oz (7.60 g)

PRODUCT DIMENSIONS



Provided by:



MICROCNX™ CONNECTORS ASSEMBLY PROCEDURE

PINCH



Remove the protective cover on each half.

CLICK



Join halves and click together.

PULL



Pull membrane strips directly away from the connector.

WARRANTY: All sales are subject to Colder Products Company's limited express warranty set forth in the CPC catalog. Contact your local distributor or CPC Customer Service for warranty provisions.

Warning: Due to the wide variety of possible fluid media and operating conditions, unintended consequences may result from the use of this product, all of which are beyond the control of CPC. It is the user's responsibility to carefully determine and test for compatibility for use with their application. All such risks shall be assumed by the buyer.

COPYRIGHT © 2021 BY COLDER PRODUCTS COMPANY. COLDER PRODUCTS COMPANY, COLDER PRODUCTS AND CPC ARE REGISTERED

TRADEMARKS WITH THE US PATENT & TRADEMARK OFFICE

SPEC1067 8/21